

BVF Self Contained Breathing Apparatus

BVF is a Self Contained Breathing Apparatus designed for short maintenance interventions in chemical plants and industrial areas or for escape from dangerous environments.

BVF adds the highest degree of safety and comfort to the efficiency, versatility and simple use of the **MK2 System**, as well as the astonishing field of vision of the Spasciani **TR 2002 A** mask.

BVF is fitted with an automatic demand valve which keeps a positive pressure in the mask thus avoiding any possible inward leakage of contaminated air from the outside. Should it become necessary, the positive pressure mode can be activated by acting on the special button that acts as a supplementary air command, too. The demand valve is connected to the medium pressure hose by means of a quick coupling which allows to disconnect it very easily for maintenance .

BVF takes advantage from the unique **MK2 System** warning built into the demand valve. This is activated when the pressure left in the cylinder drops below 70 bar. The signal originates from a sounding vibration caused by every inhalation. In this way the full capacity of cylinder is made available to the user for breathing. The acoustic warning is related to the respiratory frequency of the user and allows the user to distinguish his own signal from that emitted by nearby fellows or noise (**Self Test** function). The location of the warning device protects it from frost or dirt.

The supporting harnesses can be regulated and they allow to put the cylinder in the most comfortable position on the operator side or front allowing him to move even in narrow places. The pressure reducer keeps the outlet pressure constant throughout the emptying of the cylinder and is connected to an easy to read phosphorescent gauge. The steel cylinder has a capacity of 3 liters with a pressure of 300 bar and is fitted with a valve according to EN 144.

BVF can also be used in conjunction with a wheeled BA Spasciani **RC** or an air line feeding system by means of the optional 4-way valve. The BVF/A 1303 becomes in this way a back up unit that in case of lack of air from the air line automatically supplies the operator with an air reserve sufficient to leave the intervention area.

TECHNICAL DATA

Pressure Reducer: piston with compensator





BVF

Self Contained Breathing Apparatus

Automatic Demand Valve: with integral alarm device and supplementary supply button

Setting of the Alarm: 70 ± 5 bar

Volume/pressure of Cylinder: 3 l/ 300 bar

Air reserve: 830 N litres

Duration: 27 min at an average consumption of 30 l/min.

CLASSIFICATION

Certified **Type 1** to **EN137:2006** and meeting with directives **98/686/EEC (PPE)** and **97/23/EC (PED)**

MARKING



MATERIALS

Mask:	TR 2002 A
Outer face blank:	EPDM
Panoramic Visor:	Scratch and solvent resistant polycarbonate
Inner Nose Cup:	TPE
Five arm head harness:	EPDM
Carrying strap:	PVC
Harnesses:	Self-extinguishing webbing
Pressure reducer:	Brass alloy nickel plated
Automatic Demand Valve:	Fiber glass reinforced nylon housing
Cylinder:	Steel

STORAGE

Store at temperatures between -20 and +50 °C and with RH <80%

WEIGHT

9.6 Kg approx., set complete with mask and fully charged cylinder

DIMENSIONS/PACKING

310x570x210 mm, measured with set laying down on a flat surface.

The set is packed singularly in a carton box dimensions 520x350x310 mm

For more information please check the notes along with the products or the ones published on the website: www.spasciani.com

NOTE: SPASCIANI SpA does not take any responsibility for any possible and unintentional mistake and reserve the faculty of modify materials and technical characteristics of its products at any time and without any notice.

